



MAC3 presents AIRGO

The only hammer that combines high **EFFICIENCY** and high **COMFORT** at work

Patented vibro-reduced system

- ▶ 3-axis vibration level: less than 5 m/s² on all models

Hand guards

- ▶ Secured operator's hands

Easy access to inside functions

- ▶ Time saving on maintenance work

Slender cylinder

- ▶ Better view of the working area
- ▶ More comfortable working posture

Latch system

- ▶ Quick and safe tool change

Double trigger pneumatic safety

- ▶ Safe and easy grip
- ▶ Suitable for both right- and left- handed users

Fixed handles

- ▶ More accurate work
- ▶ Reduced wear parts

Integrated muffler

- ▶ Avoids spraying towards the user

Heat treatment

- ▶ No need for additional lubrication

Low compressed air consumption

- ▶ Uses 30% less air than equivalent hammers



		PAVING BREAKERS		PICK HAMMERS			
		AIRGO 15T	AIRGO 20T	AIRGO 9D	AIRGO 10D	AIRGO 13D	AIRGO 15D
Weight	kg (lb)	20,9 (46)	21,5 (47)	9 (20)	10 (22)	13 (29)	15 (33)
Length	mm (in.)	664 (26,1)	690 (27,2)	552 (21,7)	586 (23,1)	625 (24,6)	680 (26,8)
Impact rate	bpm	1000	1000	1500	1500	1000	1000
Air consumption	l/min (cfm)	1200 (42,4)	1200 (42,4)	1000 (35,3)	1000 (35,3)	< 1200 (< 42,4)	< 1200 (< 42,4)
3-axis vibration*	m/s ²	2,9	2,9	3,1	3,1	3,1	3,1
Shank size	mm (in.)	H 22 x 82 (7/8" x 3 1/4")	H 25 x 108 (1" x 4 1/4")	Screw standard shank sizes	H 22 x 82 (7/8" x 3 1/4")	Screw standard shank sizes	H 22 x 82 (7/8" x 3 1/4")

* Factor of uncertainty K=1,5. Measures carried on and certified on the 16th of April 2015 by the National Laboratory of metrology and tests (LNE) according to the standards EN ISO 28927-10, EN ISO 5349-1 and -2, EN 12096



Equipment complying with EU regulation in force.

www.mac3europe.com

10, Allée du Canal
F-42160 Saint Cyprien
France

tél : +33 (0)4 77 02 13 08
fax : +33 (0)4 77 02 20 28
email : contact@mac3europe.com