

HAMMER

PNEUMATIC TOOLS



MADE IN FRANCE

MAC

CHANGE THE RULES

A UNIQUE RETURN ON INVESTMENT ON THE MARKET



0% LUBRICATION FOR OPERATION

OPTIMIZED USE AND MAINTENANCE



100% USER SECURITY

ATTACHMENT BY LATCH OR DOUBLE THREAD SCREW



30% OPTIMIZATION OF YIELD

THANKS TO THE INTERNAL MANUFACTURING PROCESS



DESIGN



Monobloc cylinder machined in the mass

- Limited required parts
- Better resistance over time
- Optimizing performance



Direct strike on air cushion

- Reliability and longevity
- Comfort in use



Zinc-plated surface treatment

- Better corrosion protection



Treated steel

- Optimization of mechanical characteristics
- Self-lubricating for operation



Easy access distribution valve

- Easy maintenance



Latch fastener

- Speed in tool changes
- Safety for users

CLOSURES



**LATCH
HAMMER**



**DOUBLE THREAD SCREW
HAMMER**

SPECIFICATIONS

Model	Security*	Closing system	Weight kg - lb	Length mm - in.	Impact rate bpm	Air consumption l/min - cfm	Shank size Type - mm - in.
P5	O	Screwed	5 - 11	354 - 13,9	2 800	500 - 17,7	Hex - 19x50 - ¾"x2"
P5	O	Screwed	5,1 - 11,3	364 - 14,3	2 800	500 - 17,7	Con - 2 ⁹ / ₁₆ x70 - 5 ⁸ / ₈ "x2 ¾"
P5	O	Screwed	6,2 - 13,7	392 - 15,2	2 800	500 - 17,7	Rd - 24x70 - 1 ⁵ / ₁₆ "x2 ¾"
P7	O	Screwed	7 - 15,5	437 - 17,2	2 200	900 - 31,8	Rd - 24x70 - 1 ⁵ / ₁₆ "x2 ¾"
P7	O	Screwed	6,8 - 15	422 - 16,6	2 200	900 - 31,8	Rd - 23x70 - 2 ⁹ / ₃₂ "x2 ¾"
P7	O	Screwed	6,8 - 15	422 - 16,6	2 200	900 - 31,8	RdHex - 23x70 - 2 ⁹ / ₃₂ "x2 ¾"
P7	O	Screwed	7 - 15,5	420 - 16,5	2 200	900 - 31,8	Hex - 19x50 - ¾"x2"
P9	O	Screwed	8,6 - 19	460 - 18,1	1 800	1 000 - 35,3	Rd - 23x70 - 1 2 ⁹ / ₃₂ "x2 ¾"
P9	O	Screwed	8,6 - 19	460 - 18,1	1 800	1 000 - 35,3	RdHex - 23x70 - 2 ⁹ / ₃₂ "x2 ¾"
P9	O	Screwed	8,6 - 19	475 - 18,7	1 800	1 000 - 35,3	Rd - 24x70 - 1 ⁵ / ₁₆ "x2 ¾"
P9	O	Screwed	8,6 - 19	475 - 18,7	1 800	1 000 - 35,3	Rd - 25x75 - 1"x3"
P9	O	Screwed	8,6 - 19	475 - 18,7	1 800	1 000 - 35,3	Rd - 26x70 - 1 1 ¹ / ₃₂ "x2 ¾"
P9	O	Screwed	8,6 - 19	458 - 18	1 800	1 000 - 35,3	Hex - 19x50 - ¾"x2"
P9	O	Latch	9,8 - 21,6	495 - 19,5	1 800	1 000 - 35,3	Hex - 22x82 - 7 ⁸ / ₈ "x3 1 ¹ / ₄ "
P9 GP	O	Screwed	11,5 - 25,4	488 - 19,2	1 800	1 100 - 38,8	Rd - 25x75 - 1"x3"
P9 GP	O	Latch	12,8 - 26,5	507 - 20	1 800	1 100 - 38,8	Hex - 22x82 - 7 ⁸ / ₈ "x3 1 ¹ / ₄ "
P13	O	Screwed	12,9 - 28,4	529 - 20,8	1 500	1 200 - 42,4	Rd - 26x70 - 1 1 ¹ / ₃₂ "x2 ¾"
P13	O	Latch	14 - 30,9	584 - 23	1 500	1 200 - 42,4	Hex - 22x82 - 7 ⁸ / ₈ "x3 1 ¹ / ₄ "
P13	O	Screwed	13 - 28,7	540 - 21,3	1 500	1 200 - 42,4	Rd - 24x70 - 1 ⁵ / ₁₆ "x2 ¾"
P13	O	Screwed	13 - 28,7	540 - 21,3	1 500	1 200 - 42,4	Rd - 25x75 - 1"x3"

O = in option

* Unintentional immobilizer security: compulsory CE zones

For accessories, see our specific flyer

**COMPRESSED AIR
SOLUTIONS**

**CARING FOR
PEOPLE**
approach



**CARING FOR
THE PLANET**
approach



DISTRIBUTED BY:

MAC3

10 allée du canal
ZC des Landes
42160 Saint-Cyprien
FRANCE

Tel : +33 (0)4 77 02 13 08
Fax : +33 (0)4 77 02 20 28
contact@mac3.fr

